



## ZEBRA COAT ACETONE TECHNICAL DATA SHEET

First Issued: 01/09/21

Version: 5

Version Date: 10/01/2022

Product Code: BSS-ZEB/

1/1

Acetone is the standard of the industry for cleaning composite doors. It is also the recommended solvent for removing greases and waxes from surfaces which are to be bonded, repaired or primed. Acetone is a highly flammable liquid and must be handle with the same care given to other flammable liquids.

---

### **Specific Product Properties.**

Appearance - Clear water white liquid  
Specific Gravity @ 25C- 0.7860-0.7890  
Purity, Wt. % - 99.5 Min  
Water, Wt. % - 0.5 Max  
Acidity as Acetic Acid, Wt. % - 0.002 Max  
Alkalinity, Wt. % - 0.001 Max  
Non-volatile Matter, ppm - 10 Max  
Solubility - Miscible, distilled water

---

### **Storage.**

Keep out of Reach of Children. Extremely Flammable. All containers should be properly labelled to prevent accidental ingestion or improper disposal. Individuals should re-seal any partly used material back in the container. Store under cool, dry conditions away from open flames and high temperatures. For more detailed instructions on storage, please see the MSDS Sheet.

---

### **Safety & Handling.**

Acetone contains ingredients that could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. Individuals should wash with soap and water before eating, drinking, or using toilet facilities. Individuals should observe conditions of good industrial hygiene and safe working practices. For more detailed instructions on handling please refer to the MSDS Sheet.